

The Multiskin Synthetic Push fittings for multilayer pipe.

- A range of Push fittings from 14 to 26 mm.
- Multiskin Push fittings can be installed in less than 7 seconds.
- Immediate verification of the connection with the Visu-Control ring.
- No tooling required.
- Multiskin pipe must be properly calibrated and deburred with Comap dedicated tools before fitting coupling.



Advantages

Performance

- The push fit solutions make a connection possible in 7 seconds without tools, and eliminate the risks related to welding.
- Improved hydraulics with a reduction of pressure losses of 7% on average compared to the former range of synthetic crimp products.


Safety

- Visu-Control® ring allowing visual verification of a fitting (the red indicator turns white once the pipe is connected).
- Protective cap to prevent impurities from penetrating.

Technical Specifications

Multiskin system is designed for the following applications:

- Sanitary water: 5 °C to 95 °C (operating temperature) and 10 bar (maximum operating pressure).
- Heating and cooling: -10 °C to 95 °C (operating temperature) and 10 bar (maximum operating pressure).
- Rainwater: -10 °C to 95 °C (operating temperature) and 10 bar (maximum operating pressure).



Type	Dimensions		Order Code
Straight Coupling 16x2	16x2	2/150	9270P16
Straight Coupling 20x2	20x2	2/100	9270P20
Straight Coupling 26x3	26x3	2/50	9270P26

Dimensions 9270P - Straight

Type	Dimensions							
	d1 [mm]	d2 [mm]	D1 [mm]	D2 [mm]	z1 [mm]	z2 [mm]	l1 [mm]	l2 [mm]
Straight Coupling 16x2	16	16	20	20	9	9	34	34
Straight Coupling 20x2	20	20	24	24	9	9	35	35
Straight Coupling 26x3	26	26	30	30	10	9	37	37



Find more information online:[Installation and operating instructions](#)[Installation tips](#)[LCA \(Life Cycle Assessment\) MultiSkin Fittings](#)[ACS certificate](#)[DVGW certificate \(DW-8501CT0525\)](#)[DVGW certificate \(CW-8501CT0528\)](#)[KIWA certificate Fittings](#)[KIWA certificate Piping System](#)[KOMO certificate Fittings](#)[KOMO certificate Piping System](#)[NF certificate](#)[WRAS certificate](#)[PZH certificate](#)[MultiSkin ÉMI certificate HUN](#)[Certificate MultiSkin RUS](#)[Declaration of Performance HUN](#)[KIWA K110279-01 Piping System](#)[KOMO K110280-01 certificate Piping System](#)[Sintef Produktsertifikat Multiskin PPSU Push NOR](#)[9270P RFA](#)[9270P DWG](#)[9270P STEP](#)[Leaflet](#)[Z-Card](#)[LCA \(Life Cycle Assessment\) MultiSkin Fittings](#)[Professional](#)[Productivity](#)[EnsuredConnection](#)[SafetyWorkplace](#)[HVAC](#)[Design Office](#)[Tutorial](#)

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 20 210 34 97
E nl.info@aalberts-hfc.com
I comap.aalberts-hfc.com/nl